

BACKUP CAMERA SYSTEM WITH FLUSH MOUNT CAMERA AND MIRROR MONITOR

RVS - 772718

 **REAR VIEW
SAFETY**
A Safe Fleet Brand



This system is complete with a color 4.3" TFT-LCD Mirror Monitor which attaches to the windshield, replacing the existing rear view mirror inside the vehicle. The system has mirror image capability, a power harness with two camera inputs, a 120° camera with 30 foot infra-red night vision and all the wires, connectors and mounts you will need. The system is completely weatherproof with an IP68 rating, strong and reliable, shock resistant with a 15G vibration rating (highest in the industry). It comes with a full year warranty.

BACKUP CAMERA SYSTEM WITH FLUSH MOUNT CAMERA AND MIRROR MONITOR



RVS - 772718

- COMPLETELY WEATHERPROOF WITH AN IP68 RATING
- 9 INFRARED LIGHTS FOR PERFECT VISION EVEN IN THE DARKEST NIGHT
- VIEWING ANGLE OF 120° - BEST IMAGE QUALITY WITH NO BLIND SPOTS
- ATTACHES TO THE WINDSHIELD, REPLACING THE EXISTING REAR VIEW MIRROR
- 4.3" COLOR TFT DIGITAL DISPLAY - DISTANCE GRID ARE OPTIONAL AND ADJUSTABLE.



MONITOR

TYPE	TFT LCD
SCREEN SIZE	4.3"
DOT RESOLUTION	480 X 3 (RGB) X 272
DISPLAY FORMAT	16:9
DISPLAY BRIGHTNESS	400CD/m ²
VIEWING ANGLE	U&D: 100°, L&R: 120°
VIDEO INPUT	2 CHANNEL
VIDEO SOURCE	1VP - P, 75 Ω
POWER SUPPLY	DC 9V - 32V
POWER CONSUMPTION	5W
OPERATING TEMPERATURE	-20 °C ~ +75 °C
VIDEO SYSTEM	AUTO NTSC / PAL
OVERALL DIMENSIONS	10.55" (L) X 3.15" (H) X 1" (D)
WEIGHT	800G
VIBRATION RATING	5G
SYNC SYSTEM	INTERNAL

CAMERA

SENSOR	MT9V139
SENSOR FORMAT	728 (H) X 560 (V)
PICTURE ELEMENTS	307,200 PIXELS
NTSC OUTPUT	720 (H) X 480 (V)
PAL OUTPUT	720 (H) X 576 (V)
OPTICAL FORMAT	1/4 INCH
LENS	F=2.8
RESOLUTION	480 TV LINES
WATERPROOF RATING	IP68
POWER SUPPLY	DC 9V-32V
VIEW ANGLE	120°
INFRA - RED	9 PCS
AGC	AUTO
BLC	AUTO
S/N RATIO	MORE THAN 48DB
VIDEO OUTPUT	CVBS
IMPEDANCE	75 Ω
SIGNAL	1.0 VP - P
OPERATING TEMPERATURE	-40°C ~ +75°C / RH 95% MAX