

BACKUP CAMERA SYSTEM WITH WATERPROOF QUAD VIEW MONITOR

RVS - 7709900Q

REAR VIEW
SAFETY
REVERSE WITH CONFIDENCE™



This amazing waterproof backup camera system is complete with a 7" QUAD DIGITAL TFT-LCD monitor, a touch screen display which is completely waterproof with an IP69K rating (highest in the market) and is suited for any application where the monitor is exposed to water elements. The CCD camera boasts a 130° viewing angle with 18 infra-reds and an IP69K rating. The system comes with all the wires, connectors and mounts you will need. It comes with a full year warranty.

BACKUP CAMERA SYSTEM WITH WATERPROOF QUAD VIEW MONITOR

RVS - 7709900Q



- COMPLETELY WEATHERPROOF WITH AN IP69K RATING
- 7" DIGITAL TFT LCD COLOR MONITOR WITH REMOVABLE SUNSHADE
- 2.5 MM COLOR CCD CAMERAS WITH A 130° VIEWING ANGLE
- 4 CHANNEL SYSTEM ALLOWING YOU TO CONNECT AN ADDITIONAL CAMERA
- SHOCK RESISTANT WITH A 20G VIBRATION AND 100G IMPACT RATING



MONITOR

DIMENSION	7"
TV SYSTEM	NTSC/ PAL
RESOLUTION	800 X 3 (RGB) X 480
BRIGHTNESS	400 CD/M ²
CONTRAST	500 :1
VIEWING ANGLE	U: 50° / D: 60°, R/L: 70°
ASPECT RATIO	16:9
OPERATING TEMPERATURE	-10~+65°C
STORAGE TEMPERATURE	-30~+80°C
POWER SOURCE	DC 9V - 32V
POWER FOR CAMERAS	MAX. 4x300MA, 12V
DOT PITCH	0.192 (H) X 0.1805 (V)
VIDEO INPUTS	4 VIDEO INPUTS; 1 DVD INPUT
AUDIO INPUTS	4 AUDIO INPUTS; 1 DVD INPUT
VIDEO OUTPUTS	1 REC VIDEO OUTPUT
AUDIO OUTPUT	1 LIVE AUDIO OUTPUT
TOUCH SCREEN TRANSMITTANCE	≥80%
SCREEN OPERATION PRESSURE	10~110G
SCREEN RESPONSE TIME	<10MS

CAMERA

CAMERA	1/3" SHARP® COLOR CCD
PICTURE ELEMENTS	410,000 PIXELS
GAMMA CORRECTION	R=0.45 TO 1.0
IMAGE SENSOR	620 TV LINES
PIXELS	PAL: 752 (H) X 582 (V) NTSC: 811 (H) X 507 (V)
LENS	F=2.5MM
VIEW ANGLE	130 °
WATERPROOF RATING	IP69K
SYNC SYSTEM	INTERNAL SYNCHRONIZATION
INFRA - RED DISTANCE	50 FEET (18 INFRARED)
USABLE ILLUMINATION	0 LUX (IR ON)
POWER SOURCE	DC 9V - 32V
S/N RATIO	MORE THAN 48DB
ELECTRONIC IRIS	1/50, 1/160-1/100,000 SEC
VIDEO OUTPUT	1V P - P, 75 Ω
IR SWITCH CONTROL	ACDS AUTOMATIC CONTROL
VIBRATION AND SHOCK RATING	20G / 100G
OPERATING TEMPERATURE	-40 °C ~ +70 °C / RH 95% MAX
STORAGE TEMPERATURE	-40 °C ~ +85 °C / RH 95% MAX
NET WEIGHT	22 OZ