

G - SERIES BACKUP CAMERA SYSTEM  
WITH AUTO DIMMING, COMPASS  
AND TEMPERATURE  
RVS - 776718 - DCT

**REAR VIEW  
SAFETY**  
A Safe Fleet Brand

TEMPERATURE AUTO-DIMMING COMPASS



Want the convenience of a backup camera displayed on your mirror but like the features on your factory rear view mirror? With this replacement mirror monitor there will be no sacrificing! You can replace your rear view mirror, display your backup camera and still get features like auto-dimming, compass and temperature! With all these built-in features, replacing your rear view mirror has never been easier!

The backup camera is completely waterproof with an IP68 rating and boasts excellent night vision. The system includes all parts necessary for installation and a one year warranty.

# G - SERIES BACKUP CAMERA SYSTEM WITH AUTO DIMMING, COMPASS AND TEMPERATURE RVS - 776718 - DCT

**REAR VIEW  
SAFETY**  
A Safe Fleet Brand

- COMPLETELY WEATHERPROOF WITH AN IP68 RATING
- WITH AUTO DIMMING THIS MIRROR MONITOR REDUCES THE GLARE FROM REFLECTED HEADLIGHTS AND KEEPS THE DRIVER WITHOUT DISTRACTION
- SUPER BRIGHT 4.3 INCH SCREEN
- OUTSIDE TEMPERATURE DISPLAYED ON SCREEN
- NIGHT VISION PROVIDES A GREAT PICTURE AT NIGHT USING VERY LITTLE AMBIENT LIGHT



## MONITOR

SCREEN SIZE	4.3"
DOT RESOLUTION	480 X 3 (RGB) X 272
DISPLAY FORMAT	16:9
DISPLAY BRIGHTNESS	12001X
VIEWING ANGLE	U&D: 100°, L&R: 120°
TYPE	TFT LCD
VIDEO INPUT	2 CHANNEL
VIDEO SOURCE	1VP - P, 75 Ω
POWER SUPPLY	DC 9V - 32V
POWER CONSUMPTION	8W
OPERATING TEMPERATURE	-20°C ~ +75°C
VIDEO SYSTEM	AUTO NTSC/PAL
OVERALL DIMENSIONS	10.55" (L) X 3.15" (H) X 1" (D)
WEIGHT	800G
IMPACT RATING	5G
SYNC SYSTEM	INTERNAL

## CAMERA

SENSOR	MT9V139
SENSOR FORMAT	728 (H) X 560 (V)
PICTURE ELEMENTS	307,200 PIXELS
NTSC OUTPUT	720 (H) X 480 (V)
PAL OUTPUT	720 (H) X 576 (V)
OPTICAL FORMAT	1/4 INCH
GAMMA CORRECTION	R=0.45 TO 1.0
IMAGE SENSOR	480 TV LINES
LENS	2.1MM
VIEW ANGLE	170°
SYNC SYSTEM	INTERNAL SYNCHRONIZATION
NIGHT VISION	YES
USABLE ILLUMINATION	0.5 LUX
POWER SOURCE	DC 9V - 32V
S/N RATIO	MORE THAN 48DB
ELECTRONIC IRIS	1/50, 160-1/100,000SEC
VIDEO OUTPUT	1VP - P 75 Ω
VIBRATION AND SHOCK RATING	10G / 100G
OPERATING TEMPERATURE	-40°C ~ +70°C / RH 95% MAX
STORAGE TEMPERATURE	-40°C ~ +80°C / RH 95% MAX