

G - SERIES BACKUP CAMERA SYSTEM FOR DODGE

RVS - 776718 - DODGE

**REAR VIEW
SAFETY**
A Safe Fleet Brand



This Backup Camera System comes with a 718 Mirror Monitor made with a mounting bracket specific for Dodge vehicles. This monitor will fit easily onto the windshield of all Dodges without any adjustments needed. Paired with the monitor in this system is the 776 Camera which despite its small size is powerfully built to withstand all weather conditions. The G-Series monitor replaces the existing rear view mirror for a clean look. Its screen is 4.3 inches wide and pushed to the left of the mirror to be more easily viewed by the driver. For an absolute perfect backing up experience, this monitor comes with adjustable grid lines, allowing you to adjust the grid lines to be completely accurate regardless of where you mount the camera. It is controlled with illuminated touch screen buttons.

The backup camera in this system is surface mounted and can fit almost any vehicle. This slick compact design makes the camera virtually invisible. The camera has an IP68 rating which makes it completely weatherproof and boasts excellent night vision. This system comes included with all parts necessary for installation.

Note: Monitor is specific for Dodge vehicles from 2012 onwards.

G - SERIES BACKUP CAMERA SYSTEM FOR DODGE

**REAR VIEW
SAFETY**
A Safe Fleet Brand

RVS - 776718 - DODGE

- COMPLETELY WEATHERPROOF WITH AN IP68 RATING
- OEM FACTORY - LIKE MIRROR MONITOR REPLACES EXISTING REAR VIEW MIRROR
- SUPER BRIGHT 4.3" TFT LCD COLOR SCREEN
- MT9V139 COLOR CAMERA WITH A 170° VIEWING ANGLE
- SHOCK RESISTANT WITH A 10G VIBRATION AND A 100G IMPACT RATING
- 2 CHANNEL SYSTEM ALLOWING YOU TO CONNECT AN ADDITIONAL CAMERA



MONITOR

SCREEN SIZE	4.3"
DOT RESOLUTION	480 X 3 (RGB) X 272
DISPLAY FORMAT	16:9
DISPLAY BRIGHTNESS	12001X
VIEWING ANGLE	U&D: 100°, L&R: 120°
VIDEO INPUT	2 CHANNEL
VIDEO SOURCE	1VP - P, 75 Ω
POWER SUPPLY	DC 9V - 32V
POWER CONSUMPTION	8W
OPERATING TEMPERATURE	-20 °C ~ +75 °C
VIDEO SYSTEM	AUTO NTSC / PAL
OVERALL DIMENSIONS	10.55" (L) X 3.15" (H) X 1" (D)
WEIGHT	800G
IMPACT RATING	5G
SYNC SYSTEM	INTERNAL

CAMERA

SENSOR	MT9V139
SENSOR FORMAT	728 (H) X 560 (V)
PICTURE ELEMENTS	307,200 PIXELS
NTSC OUTPUT	720 (H) X 480 (V)
PAL OUTPUT	720 (H) X 576 (V)
OPTICAL FORMAT	1/4 INCH
GAMMA CORRECTION	R=0.45 TO 1.0
IMAGE SENSOR	480 TV LINES
LENS	2.1MM
VIEW ANGLE	170°
WATERPROOF RATING	IP68
SYNC SYSTEM	INTERNAL SYNCHRONIZATION
NIGHT VISION	YES
USABLE ILLUMINATION	0.5 LUX
POWER SOURCE	DC 9V - 32V
S/N RATIO	MORE THAN 48DB
ELECTRONIC IRIS	1/50, 160-1/100,000SEC
VIDEO OUTPUT	1VP - P, 75 Ω
VIBRATION AND SHOCK RATING	10G / 100G
OPERATING TEMPERATURE	-40°C ~ +70°C / RH 95% MAX
STORAGE TEMPERATURE	-40°C ~ +80°C / RH 95% MAX