

BACKUP CAMERA SYSTEM WITH 7" REPLACEMENT MIRROR MONITOR



NOTE: DETAILS MAY CHANGE
BASED ON ITEM CONFIGURATION

This amazing backup camera system is complete with a color 7" TFT-LCD Digital Rear View Mirror Monitor with distance grid lines which replaces or attaches to the existing rear view mirror inside the vehicle. The system has mirror image capability and a 3 port power harness. The CCD 130° camera with 18 Infra-reds gives 50 foot infra-red night vision. The backup camera also boasts an IP69K weatherproof rating which means it can withstand all weather conditions. The system comes with all the wires, connectors and mounts you will need. The backup camera is strong and reliable, shock resistant, with a 20G vibration and comes with a full year warranty.

Please Note: This monitor does not have a reflective glass to be used as a rear view mirror, it is a full 7" display.

BACKUP CAMERA SYSTEM WITH 7" REPLACEMENT MIRROR MONITOR



- COMPLETELY WEATHERPROOF WITH AN IP69K RATING
- 7" DIGITAL TFT LCD MIRROR MOUNT MONITOR
- 2.5 MM COLOR CCD CAMERA WITH A 130° VIEWING ANGLE
- SHOCK RESISTANT WITH A 20G VIBRATION AND 100G IMPACT RATING



NOTE: DETAILS MAY CHANGE
BASED ON ITEM CONFIGURATION

MONITOR

TYPE	TFT LCD
SCREEN SIZE	7"
DOT RESOLUTION	800 X 3 (RGB) X 480
DISPLAY FORMAT/CONTRAST	16:9 / 500:1
DISPLAY BRIGHTNESS	400CD/m ²
VIEWING ANGLE	90°
VIDEO INPUT	3 CHANNEL
VIDEO SOURCE	1VP - P, 75Ω
POWER SUPPLY	DC 9V-32V
POWER CONSUMPTION	5W
OPERATING TEMPERATURE	-30°C ~ +80° C
VIDEO SYSTEM	AUTO NTSC/PAL
OVERALL DIMENSIONS	9" (L) X 4.5" (H) X 1" (D)
WEIGHT	400G
IMPACT RATING	5G
DOT PITCH	0.192 (H) X 0.1805 (V)
SYNC SYSTEM	INTERNAL

CAMERA

SENSOR	1/3" SHARP® COLOR CCD
PICTURE ELEMENTS	410,000 PIXELS
GAMMA CORRECTION	R=0.45 TO 1.0
IMAGE SENSOR	620 TV LINES
IMAGE	PAL: 752 (H) X 582 (V) NTSC 811 (H) X 507 (V)
LENS	F=2.5MM
VIEW ANGLE	130°
WATERPROOF RATING	IP69K
SYNC SYSTEM	INTERNAL SYNCHRONIZATION
INFRA-RED DISTANCE	50 FEET (18 INFRARED)
USABLE ILLUMINATION	0 LUX (IR ON)
POWER SOURCE	DC 9V-32V
S/N RATIO	MORE THAN 48DB
ELECTRONIC IRIS	1/50, 160-1/100,000SEC
VIDEO OUTPUT	1VP - P, 75 Ω
IR SWITCH CONTROL	ACDS AUTOMATIC CONTROL
VIBRATION AND SHOCK RATING	20G / 100G
OPERATING TEMPERATURE	-40°C ~ +70°C / RH 95% MAX
STORAGE TEMPERATURE	-40°C ~ +85°C / RH 95% MAX
NET WEIGHT	22OZ