

BACKUP CAMERA SYSTEM WITH SIDE CAMERAS AND QUICK CONNECT KIT

REAR VIEW
SAFETY
REVERSE WITH CONFIDENCE™



This backup camera system is perfect for the fifth wheel or travel trailer application, allowing you to mount three cameras, two side cameras to the tow vehicle and 1 (one) backup camera to your trailer and quickly connect or disconnect them with just one cable! The system comes with 1 backup camera and 2 side-view cameras which are ideal for blind-spot viewing on a large vehicle. Included in this system is a crystal clear 7" LED Digital Panel Color monitor display with distance grid lines, a 3 channel multiplexer with automatic system switch, one (1) 130° CCD Backup Camera, two (2) 120° CCD Side Cameras and all the wires, connectors and mounts you will need. The 5th wheel rear view back up camera system is completely weatherproof with an IP69K rating. The system is strong and reliable, shock resistant with a 20G vibration rating (highest in the industry) and comes with a full year warranty.

Note: Minor details may change based on item configuration

BACKUP CAMERA SYSTEM WITH SIDE CAMERAS AND QUICK CONNECT KIT

**REAR VIEW
SAFETY**
REVERSE WITH CONFIDENCE™

- COMPLETELY WEATHERPROOF WITH AN IP69K RATING
- 7" LED DIGITAL PANEL COLOR MONITOR WITH REMOVABLE SUNSHADE
- 2.5 MM CCD COLOR CAMERA WITH A 130° VIEWING ANGLE
- 2.1 MM CCD COLOR SIDE CAMERAS WITH A 120° VIEWING ANGLE
- SHOCK RESISTANT WITH A 20G VIBRATION



MONITOR

TYPE	LED DIGITAL PANEL
SCREEN SIZE	7"
DOT RESOLUTION	800 X 3 (RGB) X 480
DISPLAY FORMAT/CONTRAST	16:09 / 500:01:00
DISPLAY BRIGHTNESS	400CD/m ²
VIEWING ANGLE	U-50° D-60° L/R-70°
VIDEO INPUT	3 CHANNEL CVBS
VIDEO SOURCE	1VP-P, 75Ω
POWER SUPPLY	DC 9V-32V
POWER CONSUMPTION	5W
AUDIO OUTPUT	0.5W SPEAKER
OPERATING TEMPERATURE	-20°C ~ +70°C
STORAGE TEMPERATURE	-30°C ~ +85°C
VIDEO SYSTEM	AUTO NTSC/PAL
OVERALL DIMENSIONS	7" (L) X 5.25" (H) X 1" (D)
WEIGHT	400G
IMPACT RATING	5G
DOT PITCH	0.1926 (H) X 0.1710 (V)
ACTIVE AREA	154.08 (H) X 85.92 (V)
SYNC SYSTEM	INTERNAL

RVS-770 CAMERA

SENSOR	1/3" SHARP® COLOR CCD
PICTURE ELEMENTS	410,000 PIXELS
GAMMA CORRECTION	R-0.45 TO 1.0
IMAGE SENSOR	620 TV LINES
PIXELS	PAL: 752 (H) X 582 (V) NTSC: 811 (H) X 507 (V)
LENS	F=2.5MM
VIEW ANGLE	130°
WATERPROOF RATING	IP69K
SYNC SYSTEM	INTERNAL SYNCHRONIZATION
INFRA-RED DISTANCE	50 FEET (18 INFRARED)
USABLE ILLUMINATION	0 LUX (IR ON)
POWER SOURCE	DC 9V-32V
S/N RATIO	MORE THAN 48DB
ELECTRONIC IRIS	1/50, 160-1/100,000 SEC
VIDEO OUTPUT	1VP-P, 75 Ω
IR SWITCH CONTROL	ACDS AUTOMATIC CONTROL
VIBRATION AND SHOCK RATING	20G / 100G
OPERATING TEMPERATURE	-40°C ~ +70°C / RH 95% MAX
STORAGE TEMPERATURE	-40°C ~ +85°C / RH 95% MAX

RVS-775 CAMERA

SENSOR	1/4" SHARP® COLOR CCD
PICTURE ELEMENTS	250,000 PIXELS
GAMMA CORRECTION	R-0.45 TO 1.0
IMAGE SENSOR	420 TV LINES, PAL: 500 (H) X 582 (V), NTSC: 510 (H) X 492 (V)
LENS	2.1MM
VIEW ANGLE	120°
SYNC SYSTEM	INTERNAL SYNCHRONIZATION
INFRA-RED DISTANCE	30 FEET (9 INFRARED)
USABLE ILLUMINATION	0 LUX (IR ON)
POWER SOURCE	DC 9V-32V
S/N RATIO	MORE THAN 48DB
ELECTRONIC IRIS	1/50, 160-1/100,000 SEC
VIDEO OUTPUT	1VP-P, 75 Ω
IR SWITCH CONTROL	ACDS AUTOMATIC CONTROL
VIBRATION & SHOCK RATING	20G / 100G
OPERATING TEMPERATURE	-40°C ~ +80°C / RH 95% MAX
STORAGE TEMPERATURE	-40°C ~ +60°C / RH 95% MAX

Note: Minor details may change based on item configuration