

BACKUP CAMERA SYSTEM WITH QUAD VIEW MONITOR

REAR VIEW
SAFETY
REVERSE WITH CONFIDENCE™



NOTE: SYSTEM MAY CHANGE BASED ON ITEM CONFIGURATION

This system is complete with a crystal clear 7" OR 9" DIGITAL TFT LCD color monitor with Quad View Mode and mirror image capability, two (2) side cameras with 120° viewing angles and 30 foot infra-red night vision, one (1) OR two (2) heavy duty backup cameras with 130° viewing angles and 50 foot infra-red night vision and all the wires, connectors and mounts you will need. The cameras are completely weather proof with an IP69K rating, strong and reliable, shock resistant, with a 20G vibration rating (highest in the industry). The system comes with a full year warranty.

BACKUP CAMERA SYSTEM WITH QUAD VIEW MONITOR

**REAR VIEW
SAFETY**
REVERSE WITH CONFIDENCE™

- COMPLETELY WEATHERPROOF WITH AN IP69K RATING
- 7" OR 9" DIGITAL QUAD VIEW TFT LCD COLOR MONITOR
- 2.1 MM CCD COLOR BACKUP CAMERAS WITH A 130° VIEWING ANGLE
- 2.1 MM CCD COLOR SIDE CAMERAS WITH A 120° VIEWING ANGLE
- SHOCK RESISTANT WITH A 20G VIBRATION AND 100G IMPACT RATING



NOTE: SYSTEM MAY CHANGE BASED ON ITEM CONFIGURATION

MONITOR

TYPE	TFT LCD
SCREEN SIZE	7" [9"]
DOT RESOLUTION	800 X 3 (RGB) X 480
DISPLAY FORMAT/CONTRAST	16:9 / 500:1
DISPLAY BRIGHTNESS	400CD/m ²
VIEWING ANGLE	U50° D60° L/R70°
VIDEO INPUT	4 CHANNEL
VIDEO SOURCE	1VP-P, 75Ω
POWER SUPPLY	DC 12V-24V (+/- 10%)
POWER CONSUMPTION	5W
OPERATING TEMPERATURE	-30°C ~ +80°C
VIDEO SYSTEM	AUTO NTSC/PAL
OVERALL DIMENSIONS	7" (L) X 5.25" (H) X 1" (D) [9" (L) X 6.1" (H) X 1" (D)]
WEIGHT	400G [450G]
VIBRATION RATING	5G
ACTIVE AREA	154.08 (H) X 86.58 (V)
SYNC SYSTEM	INTERNAL

*Attributes with one value are the same on 7" and 9" monitor

RVS-770 CAMERA

SENSOR	1/4" SHARP® COLOR CCD
PICTURE ELEMENTS	250,000 PIXELS
GAMMA CORRECTION	R=0.45 TO 1.0
IMAGE SENSOR	600 TV LINES, PAL: 500 (H) X 582 (V), NTSC: 510 (H) X 492 (V)
LENS	2.1MM
VIEW ANGLE	130°
WATERPROOF RATING	IP69K
SYNC SYSTEM	INTERNAL SYNCHRONIZATION
INFRA-RED DISTANCE	50 FEET (18 INFRARED)
USABLE ILLUMINATION	0 LUX (IR ON)
POWER SOURCE	DC 12V-24V (+/- 10%)
S/N RATIO	MORE THAN 48DB
ELECTRONIC IRIS	1/50, 160-1/100,000SEC
VIDEO OUTPUT	1VP-P, 75Ω
IR SWITCH CONTROL	ACDS AUTOMATIC CONTROL
VIBRATION AND SHOCK RATING	20G / 100G
OPERATING TEMPERATURE	-40°C ~ +80°C / RH 95% MAX
STORAGE TEMPERATURE	-40°C ~ +60°C / RH 95% MAX
NET WEIGHT	220Z

RVS-775 CAMERA

SENSOR	1/4" SHARP® COLOR CCD
PICTURE ELEMENTS	250,000 PIXELS
GAMMA CORRECTION	R=0.45 TO 1.0
IMAGE SENSOR	420 TV LINES, PAL: 500 (H) X 582 (V) NTSC: 510 (H) X 492 (V)
LENS	2.1MM
VIEW ANGLE	120°
SYNC SYSTEM	INTERNAL SYNCHRONIZATION
INFRA-RED DISTANCE	30 FEET (9 INFRARED)
USABLE ILLUMINATION	0 LUX (IR ON)
POWER SOURCE	DC 12V-24V (+/- 10%)
S/N RATIO	MORE THAN 48DB
ELECTRONIC IRIS	1/50, 160-1/100,000SEC
VIDEO OUTPUT	1VP-P, 75Ω
IR SWITCH CONTROL	ACDS AUTOMATIC CONTROL
VIBRATION AND SHOCK RATING	20G / 100G
OPERATING TEMPERATURE	-40°C ~ +80°C / RH 95% MAX
STORAGE TEMPERATURE	-40°C ~ +60°C / RH 95% MAX