Mobile DVR 2 Channel AHD Mobile DVR **RVS-2200**

This compact DVR can record up to two cameras and can output the video feeds to view on a monitor. It records in MP4 compression and can handle resolution up to 1280 x 720 for each channel. Footage records onto an SD card (not included) which can be lock protected to avoid tampering. The 2200 accepts SD cards up to 512GB. It has loop recording and alarms that can be set to trigger the recording on and off.



NOTE: This DVR is equipped with two 5 pin camera connections. In order to use an RCA camera, you need an RCA adapter. **NOTE**: This DVR is only compatible with our standard or AHD cameras, not FHD.

| Specifications | | Recording & Playback Audio | 8KB/s |
|--|---|---------------------------------------|--|
| Main processor | Hi3520DV300 | Bit Rate | 010/5 |
| Operating System | Embedded Linux OS | Storage Media | SD card |
| Operating Language | Chinese/English | Video Inquiry | Inquiry by channel/Recording type |
| Operating Interface | GUI, support mouse | Local Playback | Playback by file |
| Password Security | User Password / Admin Password | Firmware Upgrading Mode | Manual/Automatic/Remote |
| Video Standard | PAL/NTSC | Firmware Upgrading Method | USB disk/Wireless network/SD card |
| Video Compression | H.264 | AV Input | 2ch aviation interface |
| Image Resolution | 720P/960H/D1/CIF | SD Card | 1 Micro SD card (up to 512 GB) |
| Playback Quality | 720P/960H/D1/CIF | USB Interface | 1 USB 2.0 (support U disk/mouse/upgrade |
| Compound Mode | A variety of ways | Ignition Input | 1 ACC signal |
| Image Display | Single/Split/QUAD display optional | UART | 1 LVTTL Level |
| Audio Compression | G.711 | LED Indication | PWR/RUN |
| Audio Recording | Audio & Video synchronized recording | Disk Lock | 1 |
| Video | 2-Channel aviation-type VIDEO | Debug Port | 1 |
| Audio | 2-Channel aviation-type AUDIO | Power Input | Minimum 9.6V DC |
| Video Output | Aircraft | Power Output | 5V 300mA |
| Recording Mode | Manual/Alarm | Power Consumption | Standby 3mA Maximum consumption 15W |
| Recording & Playback Video Bit Rate | Full frame 4096Mbps, 6 classes image quality optional | Working Temperature | @12V1.5A @24V 0.7A -25°C ~ +80°C/RH 95Max |
| Dit nato | ομισια | Storage | 720P: 1G/h/channel 960H: 750Mb/h/channel |

Copyright ©2019 Safe Fleet and its subsidiaries. All rights reserved. No part of this publication may be reproduced by any means without written permission from Safe Fleet. The information in this publication is believed to be accurate. However, Safe Fleet does not make any representation or warranty to that effect and does not assume responsibility for any consequences resulting from use of such information. Revisions or new editions of the publication may be issued (or not issued) in our discretion to incorporate such changes.



Rear View Safety, 1797 Atlantic Ave., Brooklyn NY 11233 800.764.1028 sales@rearviewsafety.com www.rearviewsafety.com

