

# Backup Camera System



## Backup Camera System with 5" Monitor

### RVS-7706035

This backup camera system is equipped with a crystal clear 5" TFT DIGITAL LCD Color Monitor with optional distance grid lines. It can connect up to 3 cameras with automatic system switch. The system includes one 130° CCD camera with 50 foot infra-red night vision and all the wires, connectors and mounts you will need. The rear view system is completely weatherproof with an IP69K rating, strong and reliable, shock resistant, with a 5G Vibration and 400G Impact Rating (highest in the industry). It comes with a full year warranty.



- COMPLETELY WEATHERPROOF CAMERA WITH AN IP69K RATING

- 5" DIGITAL TFT LCD COLOR MONITOR

- 1/3" SHARP® COLOR CCD, 410K PIXELS, 2.5 MM WIDE LENS WITH 130° ANGLE

- 3 CHANNELS ALLOWING YOU TO CONNECT ADDITIONAL CAMERAS

- SHOCK RESISTANT WITH A 5G VIBRATION AND 400G IMPACT RATING



Rear View Safety, 1797 Atlantic Ave., Brooklyn NY 11233  
800.764.1028 sales@rearviewsafety.com  
[www.rearviewsafety.com](http://www.rearviewsafety.com)

844.258.8178  
[safefleet.net](http://safefleet.net)



# Backup Camera System



## Backup Camera System with 5" Monitor

### RVS-7706035



Monitor	
Type	TFT LCD
Screen Size	5"
Dot Resolution	800 X 3 (RGB) X 480
Display Format/Contrast	16:9 / 500:1
Display Brightness	300cd/m <sup>2</sup>
Viewing Angle	U:40° D:40° L/R:70°
Video Input	3 Channel
Video Source	1Vp-p, 75Ω
Power Supply	DC 9V-32V
Power Consumption	5W
Operating Temperature	-20°C ~ +70° C
Video System	Auto NTSC/PAL
Overall Dimensions	5" (L) x 5" (H) x 1" (D)
Weight	400G
Vibration Rating	5G
Impact Rating	400G
Dot Pitch	154.08 (H) X 86.58 (V)
Sync System	Internal
Overall Dimensions	5.25" (H) x 7" (L) x 1.5" (D)

Camera	
Sensor	1/3" Sharp® Color CCD
Picture Elements	410,000 pixels
Gamma Correction	r=0.45 to 1.0
Image Sensor	620 TV lines
Pixels	PAL: 752 (H) x 582 / NTSC: 811 (H) x 507 (V)
Lens	f=2.5mm
View Angle	130°
Waterproof Rating	IP69K
Sync System	Internal Synchronization
Infra-red distance	50 Feet (18 Infrared)
Usable Illumination	0 Lux (IR On)
Power Source	DC 9v-32v
S/N Ratio	More than 48dB
Electronic Iris	1/50, 160-1/100,000sec
Video Output	1Vp - p, 75 Ω
IR Switch Control	ACDS Automatic Control
Vibration and impact Rating	20G / 100G
Operating Temperature	-40°C ~ +70°C / RH 95% Max
Storage Temperature	-40°C ~ +85°C / RH 95% Max
Net Weight	22oz