

inView 360° System



360° Non-Recording Around Vehicle Monitoring System

RVS-360V2

The inView 360° Around Vehicle Monitoring System greatly reduces blind spots by giving drivers a real-time 360° view around the apparatus. The RVS-360V2 is equipped with 4 Full HD ultra-wide fish-eye cameras, which give four unique views that seamlessly merge together to create a complete image of your vehicle and its surroundings. Use the 360° view to assist with parking, check blind spots, or navigate narrow roads. The RVS-360V2 easily integrates with our 7" or 10" HD monitor. The system comes with auto-calibration, so the entire calibration process can be done in as little as ten minutes! Unlike the RVS-02-360, the RVS-360V2 comes without DVR, so you get all the benefits of a bird's-eye-view and auto-calibration at a much lower price point.



■ Full Around Vehicle Monitoring (AVM)

The standard system consists of four cameras to provide a 2D, four camera stitched-around-vehicle view (top view). The system is capable of connecting another 1-2 cameras to monitor other areas.

■ AUTOMATIC TRIGGERS

Set triggers to have the camera view change automatically (left/right/reverse/default).

■ CUSTOMIZABLE ON SCREEN OVERLAY

Customize the width, length, and position of the overlay for specific applications.

■ AUTO CALIBRATION

Calibration is performed simply and easily, directly through the system monitor.

■ ADVANCED FEATURES

The RVS-360V2 has a built-in G-Sensor.

■ INSTANT REVERSE

The system activates the rear camera image with 2 seconds of ignition, enabling FMVSS-111 compliance.



Rear View Safety, 1797 Atlantic Ave., Brooklyn NY 11233
800.764.1028 sales@rearviewsafety.com
www.rearviewsafety.com

844.258.8178
safefleet.net



inView 360° System



360° Non-Recording Around Vehicle Monitoring System

RVS-360V2

System Components:



Electronic Control Unit (ECU)



Ultra-wide Camera with Housing (x4)



7"/>" HD Monitor (optional)



External IR Sensor



Push Button



Passive CVBS Splitter

System	
Operating Voltage	8 VDC to 32 VDC. Reverse polarity protection on power
Operating Temperature	-20°C to 70°C
Storage Temperature	-40°C to 85°C
Self-Diagnostics	On boot. LED indicators, on-screen indicators
Views:	Top View, 2D stitched around vehicle view / Front / Reverse / Left / Right
	Top view combined with one of the following views Front / Reverse / Left / Right
	Auto-switched based on external signal triggers: Left / Right / Reverse Signals
	Manual-switched with an external push button
	Instantaneous reverse view after engine ignition and reverse gear engaged
Bulk Calibration	Supported
Trigger Signal Voltage	6 to 32 VDC
Configuration	Via IR, via monitor (touch screen or mouse driven)
Frame Rate	1080p @30fps NTSC, @25fps PAL; all channels
Compression/Encoding	H.264
Monitor	Supports 720p (CVBS) and /or 1080p (HD); touch screen capable
Video Streaming	RTSP support via ethernet
Vehicle Image Library	Editable - Preloaded with 8 vehicle types

ECU	
Enclosure	Enclosure: die-cast aluminum ADC12; lockable / removable front cover (metal).
Video Outputs	1080p / CVBS, 2 ports
Video Inputs	Up to 6; 4 cameras to provide top view, 2 spare channels
Trigger Signals	Left / Right / Reverse / Panic (event marking), 6-32VDC @ 0.12 to 0.63 mA.
Camera Port Impedance	75 Ω
Video Output Port Impedance	75 Ω
Dimensions	135 x 120 x 40 mm; 5.8 x 6.8 x 1.5 in
IR Sensor	3m extension
Camera	
Enclosure	Die-cast aluminum ADC12 with a 304 stainless steel bracket; IP69K-rated
Dimensions	52 x 42 x 40 mm; 2.0 x 1.7 x 1.6 in (approximate)
Sensor	2.9 mega-pixel CMOS
Power	ECU-supplied
Voltage	12VDC @65 mA
Focal Length	2.8mm
Field of View (FOV)	130° (V) x 190° (H)
SNR	>80dB
Other	
G-Sensor	Equipped; Built-In
Language	English / French / German / Dutch
Units of Measure	Metric / Imperial
Ports	USB / RS232C / RS485 / Can Bus
Homologation	FCC / EMark / CE