## All-In-One Radar + Camera System(RC-01) HANSCOM K.

## All-In-One radar with camera system






Option: Radar monitor

## **Features**

- All-In-One radar camera
- Provide image and audible waring signal
- 24GHz FMCW technology
- 1080P (Full HD)/ F.O.V :140°
- Night vision (IR LED & CDS sensor)
- TDN: True Day & Night
- Directional Sensing to minimize false alarm
- Detection range: 4 3x 4.0 meter
- Waterproof and rugged design



## Description

The All-In-One radar camera uses 24GHz FMCW technology to detect stationary object and people in blind spots. The radar integrated camera provide both blind spot image and audible waring to the driver to prevent accidents. It assist drivers by notifying them of other vehicle as well as obstacles they may miss. You do not have to install camera and radar respectively. Just install housing and connect one cable from radar to the radar monitor. The smallest radar integrated camera system is commercial grade as well as IP 69K waterproof rating.

| Model                      | Camera Spec  |
|----------------------------|--|
| Image Sensor               | 1/2.9" SONY Progressive Scan CMOS Image Sensor       |
| Total Pixels               | 2000(H) X 1121(V)                                    |
| Number of effective pixels | 1984(H) X 1105(V) , 2.19MP                           |
| Video Signal System        | AHD , Internal , Option (CVBS ,960H)                 |
| Max, Video Resolution      | 1080p@30fps/25fps                                    |
| Minimum Illumination       | 0Lux (With IR LED) , 6Lux : LED ON , 25Lux : LED OFF |
| Lens                       | F2.0 , 2.9mm 140°                                    |
| Model                      | Radar Spec   |
| Transmit frequency         | 24.05 ~ 24.20GHz (EU, FCC, KC)                       |
| Modulation                 | FMCW(Frequency Modulated Continuous Wave )           |
| Detection time             | Under 200ms  |
| Communication              | RS-485   |
| Power Input range          | 12V ~ 30V  |
| Power Consumption          | TBD  |
| Operating Temp             | -30°C ~ 85°C   |
| Storage Temp               | -40°C ~ +85°C  |
| Size                       | 117 x 59(H) x 72.5                                   |
| Weight                     | TBD  |