

BACKUP CAMERA SYSTEM



NOTE: MINOR DETAILS MAY CHANGE
BASED ON ITEM CONFIGURATION

This backup camera system is complete with a crystal clear 7" LED Digital Panel color monitor with distance grid lines and mirror image capability, 130° SHARP® CCD backup camera with 50 foot infra-red night vision and all the wires, connectors and mounts you will need. The rear view camera system is completely weather proof with an IP69K rating, strong and reliable, shock resistant, with a 20G vibration and 100G shock rating (highest in the industry). It comes with a full year warranty.

BACKUP CAMERA SYSTEM



A Safe Fleet Brand

- COMPLETELY WEATHERPROOF WITH AN IP69K RATING
- 7" LED DIGITAL PANEL COLOR MONITOR WITH MIRROR IMAGE CAPABILITY
- 1/3 SHARP® COLOR CCD, 410K PIXELS, 2.5 MM WIDE LENS WITH 130° ANGLE
- SHOCK RESISTANT WITH A 20G VIBRATION AND 100G IMPACT RATING



NOTE: MINOR DETAILS MAY CHANGE
BASED ON ITEM CONFIGURATION

MONITOR

PANEL SIZE	7" LED DIGITAL PANEL
DOT RESOLUTION	800 X 3 (RGB) X 480
SCREEN MODE	16:09
CONTRAST RATIO	500:01:00
DISPLAY BRIGHTNESS	450CD/m ²
FIELD OF VIEW	U:50° D:60° L/R:70°
CAMERA INPUT	3 CHANNEL
VIDEO SOURCE	1VP-P, 75Ω
POWER SUPPLY	DC 9V-32V
POWER CONSUMPTION	5W
AUDIO OUTPUT	0.5W SPEAKER
OPERATING TEMPERATURE	-20°C ~ +70° C
STORAGE TEMPERATURE	-30°C ~ +85°C
VIDEO SYSTEM	AUTO NTSC/PAL
OVERALL DIMENSIONS	7" (L) X 5" (H) X 1" (D)
WEIGHT	400G
IMPACT RATING	5G
DOT PITCH	0.1926 (H) X 0.1710 (V)
ACTIVE AREA	154.08(H) X 85.92(V) MM
SYNC SYSTEM	INTERNAL

CAMERA

CAMERA	1/3" SHARP® COLOR CCD
PICTURE ELEMENTS	410,000 PIXELS
GAMMA CORRECTION	R=0.45 TO 1.0
IMAGE SENSOR	620 TV LINES
PIXELS	PAL: 752 (H) X 582 (V), NTSC: 811(H) X 507 (V)
LENS	2.5MM
VIEW ANGLE	130°
WATERPROOF RATING	IP69K
SYNC SYSTEM	INTERNAL SYNCHRONIZATION
INFRA-RED DISTANCE	50 FEET (18 INFRARED)
USABLE ILLUMINATION	0 LUX (IR ON)
POWER SOURCE	DC 9V-32V
S/N RATIO	MORE THAN 48DB
ELECTRONIC IRIS	1/50, 160-1/100,000SEC
VIDEO OUTPUT	1VP - P, 75Ω
IR SWITCH CONTROL	ACDS AUTOMATIC CONTROL
VIBRATION AND SHOCK RATING	20G / 100G
OPERATING TEMPERATURE	-40°C ~ +70°C / RH 95% MAX
STORAGE TEMPERATURE	-40°C ~ +85°C / RH 95% MAX