G - SERIES BACKUP CAMERA SYSTEM WITH BACKUP SENSORS

RVS - 776718 - PS

REAR VIEW SAFETY
A Safe Fleet Brand



Sensors and a backup camera. Now that's a good way to protect your vehicle! Both the sensors and backup camera with this system connect to the replacement mirror monitor which attaches straight to the vehicle's windshield. This mirror monitor is reflective and will act as a rear view mirror, display the backup camera and alert you audibly from the backup sensors. What a way to stay safe!

G - SERIES BACKUP CAMERA SYSTEM WITH BACKUP SENSORS

RVS - 776718 - PS

REAR VIEW SAFETY
A Safe Fleet Brand

- COMPLETELY WEATHERPROOF WITH AN IP68 RATING
- OEM FACTORY - LIKE MIRROR MONITOR REPLACES EXISTING REAR VIEW MIRROR
- SUPER BRIGHT 4.3" TFT LCD COLOR SCREEN
- MT9V139 COLOR CAMERA WITH A 170° VIEWING ANGLE
- SHOCK RESISTANT WITH A 20G VIBRATION AND A 100G IMPACT RATING



MONITOR

SCREEN SIZE	4.3"
DOT RESOLUTION	480 X 3 (RGB) X 272
DISPLAY FORMAT	16:9
DISPLAY BRIGHTNESS	12001X
VIEWING ANGLE	U&D: 100° , L&R: 120°
VIDEO INPUT	2 CHANNEL
VIDEO SOURCE	1VP - P, 75 Ω
POWER SUPPLY	DC 9V - 32V
POWER CONSUMPTION	8W
OPERATING TEMPERATURE	-20 °C ~ +75 °C
VIDEO SYSTEM	AUTO NTSC / PAL
OVERALL DIMENSIONS	10.55" (L) X 3.15" (H) X 1" (D)
WEIGHT	800G
IMPACT RATING	5G
SYNC SYSTEM	INTERNAL

CAMERA

SENSOR	MT9V139
SENSOR FORMAT	728 (H) X 560 (V)
PICTURE ELEMENTS	307,200 PIXELS
NTSC OUTPUT	720 (H) X 480 (V)
PAL OUTPUT	720 (H) X 576 (V)
OPTICAL FORMAT	1/4 INCH
GAMMA CORRECTION	R=0.45 TO 1.0
IMAGE SENSOR	480 TV LINES
LENS	2.1MM
VIEW ANGLE	170°
WATERPROOF RATING	IP68
SYNC SYSTEM	INTERNAL SYNCHRONIZATION
NIGHT VISION	YES
USABLE ILLUMINATION	0.5 LUX
POWER SOURCE	DC 9V - 32V
S/N RATIO	MORE THAN 48DB
ELECTRONIC IRIS	1/50, 160-1/100,000SEC
VIDEO OUTPUT	1VP - P, 75 Ω
VIBRATION AND SHOCK RATING	10G / 100G
OPERATING TEMPERATURE	-40°C ~ +70°C / RH 95% MAX
STORAGE TEMPERATURE	-40°C ~ +80°C / RH 95% MAX

Rear View Safety | 1797 Atlantic Avenue | Brooklyn NY 11233 | 800.764.1028 | Sales@RearViewSafety.com | www.RearViewSafety.com