

# G-Series Backup Camera System With Built-in Hidden Dash Camera

RVS-776718-HBB

REAR VIEW  
**SAFETY**  
A Safe Fleet Brand



The monitor with this backup camera system not only provides the view of the backup camera on its 4.3" screen but also comes with a built-in hidden dash camera to record full HD video out the front windshield. An SD card slot allows recordings on SD cards up to 32GB and when card is full, recording will loop and start overwriting the oldest footage. This system also includes parking mode, motion detection and a G-Sensor for event recording.

The backup camera with this system is small and compact yet powerful with a 170° viewing angle and a completely waterproof encasing with an IP68 rating.

# G-Series Backup Camera System With Built-in Hidden Dash Camera RVS-776718-HBB

- 4.3" Replacement Mirror Monitor
- Hidden Dash Camera Records HD Footage Out Front Windshield
- Dash Camera Equipped with Loop Recording and G-Sensor
- 170° Ultra Wide Viewing Angle and Excellent Night Vision



## MONITOR

SCREEN SIZE	4.3" (16:9 TFT DISPLAY)
CPU	AMBARELLA A7
MEMORY/FLASH	32MB/1GB
IMAGE SENSOR	CMOS OV4689-H67A
VIDEO RESOLUTION	1920X1080 30FPS 1280X720 60FPS 1280X720 30FPS
SD/TF CARD	64GB MAXIMUM CAPACITY
POWER SOURCE	DC 9V - 32V
FOCUS	12CM-INFINITE
AUDIO	BUILT-IN MICROPHONE/SPEAKER
OPERATING TEMPERATURE	-20°C ~ +65°C
DIMENSIONS	3.15" (H) X 10.55" (L) X 1" (D)

## CAMERA

SENSOR	MT9V139
SENSOR FORMAT	728 (H) X 560 (V)
PICTURE ELEMENTS	307,200 PIXELS
NTSC OUTPUT	720 (H) X 480 (V)
PAL OUTPUT	720 (H) X 576 (V)
OPTICAL FORMAT	1/4 INCH
GAMMA CORRECTION	R=0.45 TO 1.0
IMAGE SENSOR	480TV LINES
LENS	2.1MM
VIEW ANGLE	170°
SYNC SYSTEM	INTERNAL SYNCHRONIZATION
NIGHT VISION	YES
USABLE ILLUMINATION	0.5 LUX
POWER SOURCE	DC 9V - 32V
S/N RATIO	MORE THAN 48DB
ELECTRONIC IRIS	1/50, 160-1/100,000SEC
VIDEO OUTPUT	1VP - P 75 Ω
VIBRATION AND SHOCK RATING	10G / 100G
OPERATING TEMPERATURE	-40°C ~ +70°C / RH 95% MAX
STORAGE TEMPERATURE	-40°C ~ +80°C / RH 95% MAX