

G-Series Backup Camera System With Frameless Mirror Monitor and Mirrorlink RVS-776718-FLML

REAR VIEW
SAFETY
A Safe Fleet Brand



For a backup camera system which fits almost any vehicle and is virtually invisible, look no further than the G-Series Camera System. A modern take on a classic, the RVS-76718-FLML features a frameless design, mirrorlink technology and a waterproof compact camera. This touchscreen system is equipped with a 4.3" display placed to the left of the mirror while the entire surface is reflective and acts as a mirror. MirrorLink enables you to view your mobile phone on your mirror monitor through WiFi and standard programs like DLNA, Miracast and Air Play. Navigate your trip, select and listen to music, or play games on your mirror monitor, all with your cell phone!

For an absolute perfect backing up experience, this monitor comes with adjustable grid lines, allowing you to adjust the grid lines to be completely accurate regardless where you mount the camera. The camera has an IP68 rating which makes it completely weatherproof and boasts excellent night vision. This system comes included with all parts necessary for installation.

G-Series Backup Camera System With Frameless Mirror Monitor and Mirrorlink RVS-776718-FLML



- Frameless Touch Screen Mirror Monitor with 4.3" Display
- MirrorLink - View mobile phone on monitor
- 170° Ultra Wide Viewing Angle and Excellent Night Vision
- Completely Waterproof Camera - IP68



MONITOR

| | |
|---------------------|---------------------------------|
| SCREEN SIZE | 4.3" |
| DOT RESOLUTION | 480 (H) X 272 (V) |
| DISPLAY | TFT-LCD |
| WORKING VOLTAGE | 12V |
| POWER SOURCE | DC 9V - 32V |
| VIDEO INPUT | 2 CHANNEL |
| VIDEO SYSTEM | PAL/AUTO/NTSC |
| WORKING TEMPERATURE | -20°C ~ +65°C |
| BRIGHTNESS | 1100 CD/M2 |
| OVERALL DIMENSIONS | 3.15" (H) X 10.55" (L) X 1" (D) |

CAMERA

| | |
|----------------------------|----------------------------|
| SENSOR | MT9V139 |
| SENSOR FORMAT | 728 (H) X 560 (V) |
| PICTURE ELEMENTS | 307,200 PIXELS |
| NTSC OUTPUT | 720 (H) X 480 (V) |
| PAL OUTPUT | 720 (H) X 576 (V) |
| OPTICAL FORMAT | 1/4 INCH |
| GAMMA CORRECTION | R=0.45 TO 1.0 |
| IMAGE SENSOR | 480TV LINES |
| LENS | 2.1MM |
| VIEW ANGLE | 170° |
| SYNC SYSTEM | INTERNAL SYNCHRONIZATION |
| NIGHT VISION | YES |
| USABLE ILLUMINATION | 0.5 LUX |
| POWER SOURCE | DC 9V - 32V |
| S/N RATIO | MORE THAN 48DB |
| ELECTRONIC IRIS | 1/50, 160-1/100,000SEC |
| VIDEO OUTPUT | 1VP - P 75 Ω |
| VIBRATION AND SHOCK RATING | 10G / 100G |
| OPERATING TEMPERATURE | -40°C ~ +70°C / RH 95% MAX |
| STORAGE TEMPERATURE | -40°C ~ +80°C / RH 95% MAX |